


### FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Glass passivated junction
- Low forward voltage drop
- High current capability, High reliability
- Low power loss, high efficiency
- High surge current capability
- High speed switching, Low leakage
- High temperature soldering guaranteed: 260°C/10 seconds at terminals
- Component in accordance to RoHS 2011/65/EU



### SMA(DO-214AC)



### MECHANICAL DATA

- Case: JEDEC SMA(DO-214AC) molded plastic body
- Terminals: Solder Plated, solderable per MIL-STD-750, method 2026
- Polarity: Color band denotes cathode end
- Weight: 0.002ounce, 0.064 gram

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Rating at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.)

		Symbols	US1A	US1B	US1D	US1F	US1G	US1J	US1K	US1M	Units
Maximum Recurrent Peak Reverse Voltage		$V_{RRM}$	50	100	200	300	400	600	800	1000	Volts
Maximum RMS Voltage		$V_{RMS}$	35	70	140	210	280	420	560	700	Volts
Maximum DC Blocking Voltage		$V_{DC}$	50	100	200	300	400	600	800	1000	Volts
Maximum Average Forward Rectified Current		$I(AV)$	1.0								Amp
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)		$I_{FSM}$	30.0								Amps
Maximum Instantaneous Forward Voltage at 1.0 A		$V_F$	1.0			1.30		1.7			Volts
Maximum DC Reverse Current at rated DC blocking voltage	$T_A=25^{\circ}C$	$I_R$	5.0								$\mu A$
	$T_A=125^{\circ}C$		50								
Typical Thermal resistance		$R_{\theta JA}$	75								$^{\circ}C/W$
		$R_{\theta JL}$	27								
Maximum reverse recovery time(Note1)		$T_{rr}$	50					75		ns	
Typical junction capacitance(Note2)		$C_J$	15					10		pF	
Operating junction and storage temperature range		$T_J$ $T_{STG}$	-55 to +150								$^{\circ}C$

Note: 1. Test conditions:  $I_F=0.5A, I_R=1.0A, I_{RR}=0.25A$ .

2. Measured at 1MHz and applied reverse voltage of 4.0 Volts.

# RATINGS AND CHARACTERISTIC CURVES US1A THRU US1M

FIG.1-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC




FIG.2-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.6-TYPICAL JUNCTION CAPACITANCE

