

US1AS THRU US1MS


GLASS PASSIVATED JUNCTION
HIGH EFFICIENCY RECTIFIER
Reverse Voltage: 50 to 1000 Volts
Forward Current:1.0Ampere

FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Glass passivated junction
- Low forward voltage drop
- High current capability, High reliability
- Low power loss, high efficiency
- High surge current capability
- High speed switching, Low leakage
- High temperature soldering guaranteed:260°C/10 seconds at terminals
- Component in accordance to RoHS 2011/65/EU



SMAF



MECHANICAL DATA

- Case: SMAF molded plastic body
- Terminals: Solder Plated, solderable per MIL-STD-750,method 2026
- Polarity: Color band denotes cathode end

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Rating at 25°C ambient temperature unless otherwise specified. Single phase ,half wave ,60Hz,resistive or inductive load. For capacitive load, derate current by 20%.)

		Symbols	US1AS	US1BS	US1DS	US1FS	US1GS	US1JS	US1KS	US1MS	Units	
Maximum Recurrent Peak Reverse Voltage		V_{RRM}	50	100	200	300	400	600	800	1000	Volts	
Maximum RMS Voltage		V_{RMS}	35	70	140	210	280	420	560	700	Volts	
Maximum DC Blocking Voltage		V_{DC}	50	100	200	300	400	600	800	1000	Volts	
Maximum Average Forward Rectified Current		$I(AV)$	1.0								Amp	
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)		I_{FSM}	30.0								Amps	
Maximum Instantaneous Forward Voltage at 1.0 A		V_F	1.0			1.40		1.7			Volts	
Maximum DC Reverse Current at rated DC blocking voltage	$T_A=25^{\circ}C$	I_R	5.0								μA	
	$T_A=100^{\circ}C$		50									
Typical Thermal resistance		$R_{\theta JA}$	50								$^{\circ}C/W$	
Maximum reverse recovery time(Note1)		t_{rr}	50					75				ns
Typical junction capacitance(Note2)		C_J	15								PF	
Operating junction and storage temperature range		T_J T_{STG}	-55 to+150								$^{\circ}C$	

Note: 1.Test conditions: $I_F=0.5A, I_R=1.0A, I_{RR}=0.25A$.

2.Measured at 1MHz and applied reverse voltage of 4.0 Volts.

RATINGS AND CHARACTERISTIC CURVES US1AS THRU US1MS

FIG.1-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC




FIG.2-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.6-TYPICAL JUNCTION CAPACITANCE

